



MRL 2:1 – geared machine room less elevator

Duty Load (Kg)	Passengers	Speed (m/s)	Car Dimension (W x D)	Door Dimension (W x D)	Hoistway Dimension (W x D)	Pit (mm)	Headroom (mm)	Travel max no compens	Travel max compensat	Motor Power (KW)	Motor Current (A)	Lift Main Fuse (A)
630	8	1	1100x1400	2PT 900	1700X1800	1400	3700	30	40	6,8	16	20
630	8	1,6	1100x1400	2PT 900	1700X1800	1500	3800	30	40	11	24	25
800	10	1	1350x1400	2PT 900	1950X1800	1400	3700	30	40	7,5	18	20
800	10	1,6	1350x1400	2PT 900	1950X1800	1500	3800	30	40	12	25	35
1000	13	1	1100x2100	2PT 900	1700X2500	1400	3700	30	40	9,2	22	25
1000	13	1,6	1100x2100	2PT 900	1700X2500	1500	3800	30	40	15	33	35
1000	13	1	1600x1400	2PC 900	2200X1750	1400	3700	30	40	9,2	22	25
1000	13	1,6	1600x1400	2PC 900	2200X1750	1500	3800	30	40	15	33	35
1000	13	1	1600x1400	2PC 1100	2400X1750	1400	3700	30	40	9,2	22	25
1000	13	1,6	1600x1400	2PC 1100	2400X1750	1500	3800	30	40	15	33	35
1275	16	1	1200x2300	2PT 900	1950X2700	1400	3700	30	40	12	25	35
1275	16	1,6	1200x2300	2PT 900	1950X2700	1500	3800	30	40	17	36	40
1275	16	1	2000x1400	4PC 1400	2650X1800	1400	3700	30	40	12	25	35
1275	16	1,6	2000x1400	4PC 1400	2650X1800	1500	3800	30	40	17	36	40
1600	21	1	1400x2400	2PT 1100	2050X2800	1500	4000	30	40	15	33	35
1600	21	1,6	1400x2400	2PT 1100	2050X2800	1600	4100	30	40	22	47	50
1600	21	1	2100x1600	4PC 1400	2750X2000	1500	4000	30	40	15	33	40
1600	21	1,6	2100x1600	4PC 1400	2750X2000	1600	4100	30	40	22	47	50
2000	26	1	2200x1800	4PC 1400	3000X2250	1800	4500	30	40	19	41	50

MRL 1:1 – geared machine room less elevator

480	6	1	1000x1250	2PT 800	1600x1650	1200	3600	40	NA	5,5	14,5	16
630	8	1	1100x1400	2PT 900	1700x1800	1200	3600	40	NA	7,3	17,5	20