



MRL 2:1 – gearless machine room less elevator

Duty Load (Kg)	Passengers	Speed (m/s)	Car Dimension (W x D)	Door Dimension (W x D)	Hoistway Dimension (W x D)	Pit (mm)	Headroom (mm)	Travel max no compens	Travel max compensat	Motor Power (KW)	Motor Current (A)	Lift Main Fuse (A)
480	6	1	1000x1250	2PT 800	1600x1650	1400	3800	20	40	4,2	12	16
480	6	1,6	1000x1250	2PT 800	1600x1650	1500	3900	20	40	8	21	25
630	8	1	1100x1400	2PT 900	1700x1800	1400	3800	20	40	4,2	12	16
630	8	1,6	1100x1400	2PT 900	1700x1800	1500	3900	20	40	8	21	25
800	10	1	1350x1400	2PT 900	1950x1800	1400	3800	20	40	5,5	15	20
800	10	1,6	1350x1400	2PT 900	1950x1800	1500	3900	20	40	9,8	28	35
1000	13	1	1100x2100	2PT 900	1700x2500	1400	3800	20	40	6,7	18	20
1000	13	1,6	1100x2100	2PT 900	1700x2500	1500	3900	20	40	11,5	34	40
1000	13	1	1600x1400	2PC 900	2200x1750	1400	3800	20	40	6,7	18	20
1000	13	1,6	1600x1400	2PC 900	2200x1750	1500	3900	20	40	11,5	34	40
1000	13	1	1600x1400	2PC 1100	2400x1750	1400	3800	20	40	6,7	18	20
1000	13	1,6	1600x1400	2PC 1100	2400x1750	1500	3900	20	40	11,5	34	40
1275	16	1	1200x2300	2PT 900	1950x2700	1400	3800	20	40	8,9	27	35
1275	16	1,6	1200x2300	2PT 900	1950x2700	1500	3900	20	40	14,8	46	50
1275	16	1	2000x1400	4PC 1400	2650x1800	1400	3800	20	40	8,9	27	35
1275	16	1,6	2000x1400	4PC 1400	2650x1800	1500	3900	20	40	14,8	46	50
1600	21	1	1400x2400	2PT 1100	2050x2800	1500	4100	20	40	11	35	40
1600	21	1,6	1400x2400	2PT 1100	2050x2800	1600	4200	20	40	18	57	63
1600	21	1	2100x1600	4PC 1400	2750x2000	1500	4100	20	40	11	35	40
1600	21	1,6	2100x1600	4PC 1400	2750x2000	1600	4200	20	40	18	57	63
1600	21	1	2100x1600	4PC 1400	2750x2000	1500	4100	20	40	11	35	40
2000	21	1	1500x2700	4PC 1300	2200x3100	1500	4100	20	40	15	40	50
2000	21	1	1400x2800	2PT 1200	2100x3200	1500	4100	20	40	15	40	50
2000	21	1	1800x2400	4PC 1400	2500x2800	1500	4100	20	40	15	40	50
2500	21	1	1800x2700	4PC 1500	2500x3100	1500	4100	20	40	19	50	63
2500	21	1	2200x2300	4PC 1500	3000x2800	1500	4100	20	40	19	50	63